





HP EU HP Deutschland, GmbH, HQ-Technical Regulations Schickardstr. 32, 71025 Boeblingen, Germany

HP Inc UK Ltd. Regulatory Enquiries, Earley West, 300 Thames Valley Park Drive, Reading, RG6 1PT, England

© 2023 Poly. All trademarks are the property of their respective owners.



1725-88161-001A 07/23 RMN: Poly ATA 400



www.poly.com/support/ata-400

Recyclable where facilities exist

Ľ,S)

LED

(1)

 \bigcirc



Solid green: Powered on and working

Solid red: Not operational

Off: Port service not available

Flashing green: Phone in use

Solid green: Phone ready (standby)

LAN Ethernet port

Flashing green: Searching for a DHCP IP address

Flashing orange: Upgrading (Do not unplug power.)

Flashing green (fast blinking): Data activity on the

Off: No Power

YOU WILL NEED

- Touch-tone phone
- Active Internet connection
- Access to the Internet via an Ethernet port on your router or modem
- (Optional) Internet phone service subscription

ATA system web interface

- From a phone attached to the ATA device, dial *** to access the ATA config attendant.
- Choose 1 to hear the IP address of the ATA device. 2.
- 3. Enter the ATA device IP address in a local PC web browser.
- 4 When prompted, enter **admin** for the user name and **admin** for the password

